

Use No Oil Gauge

Picture



Parameter

**Model #:** YQ001

**Description:** Use no oil pressure gauge is designed for welding, medical, and compressed gas regulator service. Strictly oil-free controlled in production

**Size:** Available in size 1.5", 2", and 2.5"

**Pressure range:** 0-30, 60, 100, 200, 400, 4000, 6000, and 7500psi, other ranges available on request

**Socket:** Brass LM or CBM

**Connection thread:** 1/4"NPT or 1/8"NPT, other threads available on request

**Bourdon tube:** Phosphor bronze, silver soldered

**Case:** Polished brass, Zinc plated steel, or black ABS plastic

**Bezel:** No bezel or steel press-on bezel

**Window(Lens):** Screw-on plastic lens for Polished brass case gauge; regular plastic lens for steel/plastic case oens

**Dial:** With ALF logo or customer logo, single and dual scale (psi, kpa, bar, kg/cm<sup>2</sup>) available

**Accuracy:** +/- 3/2/3% of full scale (ASME B40.1 Grade B)

**Ambient temperature:** -40 to 60 Degrees centigrade

**UL:** High pressure UL 404 listed  
Low pressure UL252A recognized

**Explosion:** High pressure explosion protected

**Option Info:** Restrictor

Order restrictor to have a brass restrictor pressed into the socket of the gauge to reduce the size of the internal bore. The restrictor dampens the effects of pressure pulsation which in turn helps prevent internal damage to the Bourdon tube and movement and extends the life of the gauge